



CEMENT REMOVER

Strong acid compound used for removing cement residues from most common metal surfaces. It must not be used on zinc, aluminium, galvanised materials and stainless steel.

FEATURES & BENEFITS

- **Fast and efficient cement removal**
- **Non-caustic / non-phosphate**
- **Water-based**
- **Non-toxic**
- **Non-solvent, non-butyl**
- **Safe on paint, glass, plastics and most metals**
- **Strong and effective removal of cement and concrete splatter on cargo holds, machinery and equipment**
- **Cost-effective and easy to use**
- **Inhibited against attack on ferrous metals**
- **Non-flammable**
- **Safe to use on most tank surfaces and most coatings**

DIRECTIONS FOR USE

Apply CEMENT REMOVER with a brush to surfaces to be cleaned.

In general 2 - 5% dilution with water is an ideal dosage to clean cargo holds without affecting the coatings.

Use undiluted for hard cement deposits on the surfaces.

Use diluted in solution of 25 - 50%, depending on the thickness of the cement layer.

Rinse thoroughly with water after 10 - 15 minutes after application.

STANDARD PACKING

CEMENT REMOVER is usually available in plastic cans of 25 l and plastic drums of 200 l.

For product characteristics and for the nature of special risks and safety advice consult our MSDS.
www.vecom-marine.com - sales@vecom-marine.com