



# STEAMCLEAN EXTRA

STEAMCLEAN EXTRA is a strong, specialised tank cleaning product.

## FEATURES & BENEFITS

- Water-based alkaline cleaner with strong concentrated cleaning agents
- Non-flammable
- Fully biodegradable cleaner
- Lower dilution / dose rate 0.5 to 3%
- Specially designed for use with steam HP cleaners
- Suitable for cold and HP cleaners and cold steam cleaners
- Prevents clogging of the nozzles
- Can be used on RO/RO vessels to clean exhaust deposits after vehicles have been discharged
- Great engine room cleaner
- NSF approved
- Very effective for the removal of atmospheric deposits, oils and grease
- Easy to use and very cost-effective

### PRODUCT DESCRIPTION

STEAMCLEAN EXTRA is a highly-concentrated cleaning agent based on a blend of surfactants, alkalines and hardness control agents. Very effective alkaline cleaner for the removal of atmospheric deposits, oils and grease by means of steam cleaners.

Because of the addition of hardness control agents this product can be used in steam and water with a high hardness without the risk of clogging the spray nozzles of spraying equipment. As a result, it is very suitable for use in steam cleaners and high-pressure spraying equipment. The ideal combination of STEAMCLEAN EXTRA and steam enables you to clean places that are particularly difficult to reach.

The product can be used on epoxy coatings and most metals, but may NOT be used on aluminium, tin, zinc, galvanised materials, zinc silicate coatings and most paints and varnishes.

### APPLICATIONS

STEAMCLEAN EXTRA is used for removing oil, grease and dirt from machinery, chassis, tanks, containers and from floors in workshops and engine rooms.

For product characteristics and for the nature of special risks and safety advice consult our MSDS.  
[www.vecom-marine.com](http://www.vecom-marine.com) - [sales@vecom-marine.com](mailto:sales@vecom-marine.com)



## **DIRECTIONS FOR USE**

### **FOR USE IN STEAM-CLEANING EQUIPMENT**

Depending on the contamination of the parts or surfaces to be cleaned 0.5 - 3% STEAMCLEAN EXTRA is injected/sucked into the steam-cleaning equipment.

The mixture of cleaning agent and steam is subsequently atomised against the contaminated parts or surfaces with considerable force. After this cleaning procedure, any residues of cleaning agent are removed by a thorough post-steaming treatment.

### **FOR USE IN HIGH-PRESSURE SPRAYING EQUIPMENT**

Depending on the contamination of the parts or surfaces to be cleaned 0.5 - 3% STEAMCLEAN EXTRA is injected/sucked into the high-pressure steam-cleaning equipment.

The mixture of cleaning agent and water is subsequently sprayed under pressure against the contaminated parts or surfaces. After this cleaning procedure, any residues of cleaning agent are removed by a thorough post-spraying treatment with water.

## **PROPERTIES**

- Strong alkaline liquid containing sodium hydroxide.
- Can be used in hard water.
- Suitable for use on epoxy coatings and most metals, but may NOT be used on aluminium, tin, zinc, galvanised materials, zinc silicate coatings and most paints and varnishes. Odourless and non-flammable.

## **STANDARD PACKING**

STEAMCLEAN EXTRA is usually available in plastic cans of 25 l and plastic drums of 200 l.

**For product characteristics and for the nature of special risks and safety advice consult our MSDS.  
[www.vecom-marine.com](http://www.vecom-marine.com) - [sales@vecom-marine.com](mailto:sales@vecom-marine.com)**